Enter contractor's logo and name here	Company Identification	Contractor Identification	Revision Index		Sheet of Sheets
	Enter document no. from owner here	Enter document no. from contractor here	Validity Status	Rev. N.	69 / 9
				00	

Talk No: 60	Title: Tirfors, Pull-lift Jacks
Talk No. 00	This. Throis, I all like basis

Discussion points:

All persons using tirfors must ensure that the following precautions are followed:

- The Tirfor must never be released whilst under load.
- It is imperative that forward and reverse levers are not operated at the same time.
- We must ensure that the applied load has a secure anchorage.
- Always use the correct operating handle for the machine being used.
- NEVER attempt to increase the leverage by extending the operating lever with scaffold tube or similar.
- Use only the appropriate manufacturers' shear pins.
- When putting multi-sheave blocks to use, we must ensure they are suitable for the load that is being applied.
- It is important that only the specially designed wire rope supplied by the manufacturer is used.
- REMEMBER! When using a Tirfor for pulling purposes, the amount of effort required to
 move the load is not equal to the load being moved. Therefore, if the effort required is too
 great for one operative, work must cease immediately and the number of blocks
 increased (within the rated capacity of the machine).

YOUR FIRST MISTAKE CAN ALSO BE YOUR LAST!