Enter contractor's logo and name here	Company Identification	Contractor Identification	Revision Index		Sheet of Sheets
	Enter document no. from owner here	Enter document no. from contractor here	Validity Status	Rev. N.	36 / 9
				00	

Talk No: 29 Title: USE OF ABRASIVE WHEELS

Introduction: Misuse of abrasive wheels continue to result in accidents, often because the wrong type of wheel is fitted.

Main points:

- Wheels must only ever be fitted/replaced by a competent person.
- Machine speeds must never exceed the maximum permissible speed of the wheel.
- Eye and ear protection should always be worn.

Discussion points:

- Don't exert heavy pressure on wheels.
- Don't use the sides of wheels.
- Keep fingers clear of cutting edge of wheel.
- Ensure any guards are always correctly fitted and used the minimum wheel surface required for the task should be exposed. □ Be aware of other workers in the area – do not expose them to risk.
- Adjust tool rests to be as close as possible to the face of the wheel.
- Only reinforced discs should be used on hand held machines.
- Run replacement wheels for a full minute prior to using them ensuring you stand well clear.
- Always stop wheels when not in use.
- Keep the face of the wheel evenly dressed.
- Visually check wheels before use for any obvious faults if in any doubt get verification.

PPE IS NO SUBSTITUTE FOR A SAFE SYSTEM OF WORK

Notes:		